

Placement of Ducts and HVAC Systems in Conditioned Space:

An Overview

EEBA Excellence in Building Conference

October 24, 2001

Building Science Corporation
www.buildingscience.com



Building Science Corporation



Why move ducts inside?

- Energy savings from reducing forced air exchange due to duct leakage



Why move ducts inside? (continued)

- Reduce pressure imbalance problems
- Energy savings from less hostile duct environment
- Reduced heating & cooling loads—equipment downsizing




Duct Location Options

- Basement + interior walls
 - Conditioned crawl space + interior walls
 - Dropped HVAC coffer
 - Raised HVAC coffer
 - Floor truss space (two-story plans)
 - Unvented roof system
- Warning: Combustion Appliance Location**




Basement Duct System




- Standard system in many regions
- Second floor ducts must be in first floor interior walls or trunks off of floor system—not in attic.



Conditioned Crawl Space



Conditioned Crawl Space Duct System




Note: Colored shading depicts the building's thermal barrier and pressure boundary. The thermal barrier and pressure boundary enclose the conditioned space.



Conditioned Crawl Space Duct System



Dropped Ceiling Coffered Duct System




Note: Colored shading depicts the building's thermal barrier and pressure boundary. The thermal barrier and pressure boundary enclose the conditioned space.

Dropped Ceiling Coffered Duct System




Dropped Ceiling Coffered Duct System



Building Science Corporation




Raised Ceiling Coffered Duct System



BSC+2 HVAC COFFER DETAIL
NOT TO SCALE


Raised Ceiling Coffered Duct System



Raised Ceiling Coffer Duct System



Engineered Floor Truss Duct System



Note: Colored shading depicts the building's thermal barrier and pressure boundary. The thermal barrier and pressure boundary enclose the conditioned space.



Engineered Floor Truss Duct System




Engineered Floor Truss Duct System



Building Science Corporation




Engineered Floor Truss Duct System



Engineered Floor Truss Duct System



Unvented Roof Duct System



Note: Colored shading depicts the building's thermal barrier and pressure boundary. The thermal barrier and pressure boundary enclose the conditioned space.




Unvented Roof Duct System



Unvented Roof Ducts: Energy Comparisons


House 1
(Base Case)



Fully Ventilated Attic, No Ductwork in Attic, Perfect Air Barrier at Ceiling

AHU and ductwork completely inside the conditioned space


House 3



Fully Ventilated Attic, Leaky Ductwork and AHU in Attic, Imperfect Air Barrier at Ceiling

Energy performance **-15% to -30%** penalty compared with base case due to air change induced by leaky ductwork. **House 3** is the true "Base Case" for typical residential construction.


House 2



Fully Ventilated Attic, Perfectly Sealed Ductwork and AHU in Attic, Perfect Air Barrier at Ceiling

Energy performance **-3% to -6%** penalty compared with base case due to conductive losses across the ductwork and AHU.

House 4




Cost = -\$300 compared with House 3


Non-Ventilated Attic, Insulation Tight to Underside of Roof Deck, Leaky Ductwork and AHU completely inside the Conditioned Attic, Typical Ceiling Construction

Energy performance **-3% to -5%** penalty compared with base case (**House 1**). However, it allows for **15% to 25%** savings over the true base case (**House 3**).


Unvented Roof: Air Sealing Locations



Unvented Roof: Construction Detail



Unvented Roof: Construction Detail



Note: Colored components designate air flow retarder system