



Kohta Ueno
Massachusetts Deep Energy Retrofit Program: Lessons Learned





September 15, 2011






Introduction


EEBA 2011: Massachusetts DER Program: Lessons Learned
2





- ### Enclosure Retrofit
- Important target for many buildings
 - Insulation
 - Walls
 - Roof
 - Foundations
 - Windows
 - Airtightness
 - Prioritize by Ease and Impact
- EEBA 2011: Massachusetts DER Program: Lessons Learned 8

- ### Deep Energy Retrofits
- Significant upgrades are incrementally less expensive
 - Small upgrades very cost effective, but small (10-25% reductions)
 - mid-range upgrades (15-50%) usually really expensive per energy saved
 - Deep retrofits (>50%) secure buildings future
 - Allow for new styles, use, etc.
 - Leap frog current housing
- EEBA 2011: Massachusetts DER Program: Lessons Learned 9

National Grid DER Pilot Program

- Residential deep energy retrofit (DER) pilot program
- Incentives ~\$35 to \$60 K
- R-60 roof, R-40 walls, R-20 bsmt wall, U≤0.2 windows
- Eight completed projects
- 27 current active projects
- BSC provides technical guidance for program

nationalgrid THE POWER OF ACTION

EEBA 2011: Massachusetts DER Program: Lessons Learned 10

Las Vegas ≠ New England

EEBA 2011: Massachusetts DER Program: Lessons Learned 11

Delta T Comparisons

- Δ T is what drives heat loss/gain—therefore R values, energy paybacks, etc.
- “Dominant load” (heating vs. cooling dominated climates)
- Dominant Δ T much higher in cold climates (New England)—higher R value targets

EEBA 2011: Massachusetts DER Program: Lessons Learned 12

R-Value Targets

Climate Zone	Wall	Vented Attic	Compact Roof	Basement Wall	Exposed floor	Slab edge	Windows (U/SHGC)	Sub-slab
1	10	40	35	5	10	none	yes	none
2	15	50	40	10	20	5	0.35/<.25	none
3	20	50	45	10	20	7.5	0.30/<.3	5
4	25	60	45	15	30	7.5	0.30/<.35	7.5
5	35	65	50	20	40	10	0.15/--	10
6	40	75	60	25	45	15	0.15/--	15
7	40	90	65	25	45	15	0.15/--	15
8	50	100	75	35	50	20	0.15/--	20

Table 2: Current Recommended "True" Minimum R-value (+/-)³ including thermal bridging


- "True" R value: R-13 2x4 wall ≈ R-8; R-19 2x6 wall ≈ R-12
- Estimated targets—will vary with local construction costs, energy costs, client targets

Source: RR-1005: High R-Value Enclosures for High Performance Residential Buildings in All Climate Zones



Airtightness targets

- Zones 1-3: 0.25 CFM 50 per sf enclosure area
- Zones 4-6: 0.20 CFM 50 per sf enclosure area
- Zones 7-8: 0.15 CFM 50 per sf enclosure area



Source: RR-1005: High R-Value Enclosures for High Performance Residential Buildings in All Climate Zones

© 2008 BSC Building Science Corporation, 11 Bay Street North Shore, North Shore, Southold, Fortitude, Mass. 01930-0001

Construction Differences



But this talk is about New England deep energy retrofits...



Walls




Exterior Insulation Retrofits


- Going beyond nominal R-13/R-19 walls = thicker walls
- Exterior retrofit advantages
 - Insulation outboard of vulnerable structure
 - Interior is habitable during retrofit
 - Retain interior finishes (lose exterior finishes)
 - No loss in interior square footage
 - Can inspect condition of enclosure (during cladding removal)
 - Interior stairwells (code minimum widths)




4" Polyisocyanurate Foam



4" Polyisocyanurate Foam



EEBA 2011: Massachusetts DER Program: Lessons Learned
19

4" Polyisocyanurate Foam



EEBA 2011: Massachusetts DER Program: Lessons Learned
20

Foam Sheathing Cladding Attachment


250 lbs/113 kg load (7.8 psf): <math><0.003''</math> deflection
 Wood siding ~2 psf
 Fiber cement 2-3 psf
 Stucco 8-10 psf
 Image c/o Petersen Engineering


EEBA 2011: Massachusetts DER Program: Lessons Learned
21


Foam Sheathing Cladding Attachment



EEBA 2011: Massachusetts DER Program: Lessons Learned
22

Exterior Retrofit Complications



EEBA 2011: Massachusetts DER Program: Lessons Learned
23

4-1/2" High Density Spray Foam




EEBA 2011: Massachusetts DER Program: Lessons Learned
24




EIFS Overclad



- Insulation
- Protection of existing wall
- Aesthetic improvement?



MA DER Program: Lessons Learned

Metal Panel Overclad










Massachusetts DER Program: Lessons Learned


Roofs



EEBA 2011: Massachusetts DER Program: Lessons Learned

Fully Ventilated Attics

- Can re-roof whenever, with whatever
- Deal with moisture, then add insulation
 - Rain leaks, air leaks
- If possible, keep ventilated attic
 - Inspect ceiling plane, plug all holes with caulking and foam
 - Consider 1" of spray foam air barrier
 - Blow in minimum R60 cellulose, R75-R100 sensible



EEBA 2011: Massachusetts DER Program: Lessons Learned

Fully Ventilated Attics








EEBA 2011: Massachusetts DER Program: Lessons Learned

Fully Ventilated Attics








EEBA 2011: Massachusetts DER Program: Lessons Learned

Why an Unvented Roof?

- Difficult air barrier to retrofit @ ceiling plane?
- Leaky ductwork and AHU in attic?
- More space (dormers, bedrooms in attic?)









EEBA 2011: Massachusetts DER Program: Lessons Learned

38

Why an Unvented Roof?









EEBA 2011: Massachusetts DER Program: Lessons Learned

38

Why an Unvented Roof?


Note: Colored shading depicts the building's thermal barrier and pressure boundaries.




EEBA 2011: Massachusetts DER Program: Lessons Learned

39

Unvented Roof: How?




- 2006 IRC: R806.4 Unvented attic assemblies
- Minimum R-value of "air impermeable insulation"
- Zone 2B/3B + tile roof: none required
- Nail base needed with rigid foam on roof deck



EEBA 2011: Massachusetts DER Program: Lessons Learned

40

Windows



EEBA 2011: Massachusetts DER Program: Lessons Learned

41

Water Control: Pan Flashings





- Deep energy retrofits (addition of insulation at existing wall) can make the wall more vulnerable to water leakage
- Previously "survivable" leaks may no longer be able to dry out.



EEBA 2011: Massachusetts DER Program: Lessons Learned

42

Retrofitting "Superwindows"




U=0.25 to ~0.18 for triple glazed + low E films + Krypton fill gas + warm edge spacers

Comparison U=0.35 double glazed, low E, fill gas (?)



"Innie" vs. "Outie" Windows


- "Outie" Advantages
 - Simpler drainage plane connections/geometry
 - Lower cost (extension trim is interior material)
 - Similar appearance to conventional construction



b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 45

"Innie" vs. "Outie" Windows

- "Innie" Advantages
 - Window supported by lumber frame (foam install)
 - Greater protection from wind-driven rain (inset)
 - Less condensation risk (?)
 - Can use existing window trim
 - Solar shading (advantage or disadvantage)



b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 46

"Outie" Window Installation Options



Housewrap layer

XPS Layer 2

Housewrap layer

XPS Layer 1

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 47

Foundations

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 48

Basement Insulation Location

Building Enclosure Components:

1. Base Floor System(s)
2. Foundation Wall System(s)
3. Above Grade Wall System(s)
4. Windows and Doors
5. Roof System(s)

Legend:
 — Building Enclosure
 - - - - - Interior Spatial Separators

49

Basement Insulation Location

- 4.6 ACH50; 2129 CFM 50 total; 1100 CFM 50 through floor
- 8.5 ACH50; 3590 CFM 50 total; 1740 CFM 50 through floor

EEBA 2011: Massachusetts DER Program: Lessons Learned 50

Insulation Location Choices

- Retrofits: interior insulation is often the only available option

Internally insulated Basement Externally insulated Basement Basement Insulated in the Middle Basement Insulated Both Externally and Internally

EEBA 2011: Massachusetts DER Program: Lessons Learned 51

Basement Insulation Problems

- Wintertime interior moisture condensation (like above-grade walls)
- Condensation at bottom of wall (thermal lag of soil)
- Lack of drying of assembly (moisture from concrete and soil); soil is at 100% RH
- Liquid water through wall

EEBA 2011: Massachusetts DER Program: Lessons Learned 52

Recommended Wall Assembly


- XPS is moisture tolerant
- Wintertime condensation controlled
- Summertime (bottom of wall) condensation controlled
- Concrete can dry through XPS at a safe rate

Massachusetts DER Program: Lessons Learned 53

Frame Plaster/lath interior lining Blown cellulose cavity fill
 Clapboards Timber frame
 Flossen paper Board sheathing 3" spray polyurethane foam (2 lb/ft³ density)
 2" extruded polystyrene (XPS) frost heave protection Intumescent coating
 Membrane capillary break/drainage plane
 Concrete patch Existing slab Epoxy top coat
 Stones (no fines) Geotextile liner Drain tile (drained to sump or to daylight)

EEBA 2011: Massachusetts DER Program: Lessons Learned 54


Interior Rubble Retrofit



b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 55

Alternate Details

- Insulated slab on top of existing slab
- No membrane up wall surface
- Wet vs. dry basement?
- Light gauge steel framing interior wall



b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 56

Spray foam basement insulation

- Open cell
 - Climate specific
- Closed cell



b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 57

Spray Foam “Bathtub”

© 2011 by Byggmeister; reprinted with permission






b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 58

Air Barriers

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 59

Retrofitting Exterior Air Barriers

		
Bedford, MA “Farmhouse”	Arlington, MA “Duplex”	Jamaica Plain, MA
6.2 ACH 50	5.0 ACH 50	2.4 ACH 50
No secondary air barrier (housewrap w. connections); mediocre roof-wall connections	Basement compartmentalized? (1000 CFM 50 vs. 2129 CFM 50 total)	Vented space under existing slate roof; spray foam. All spray foam basement (“bathtub”). No clear failure points.

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 60



Retrofitting Exterior Air Barriers


		
St. Agatha, ON	Belmont, MA	Northampton, MA
~1 ACH 50	0.7 ACH 50	0.75 ACH 50
Spray foam on exterior; all windows well air sealed; casement/awning typical	Rigid foam as air barrier, "chainsaw" retrofit of roof overhangs/eaves, meticulous air barrier, blower door tests in progress	Taped ZIP wall air barrier layer roof & walls; spray foam basement, 40% new construction

 EEBA 2011: Massachusetts DER Program: Lessons Learned 61

Retrofitting Exterior Air Barriers



- Other projects in 1.5 ACH 50 range; ~3-5 ACH 50 outliers, under 1 as well
- Roof-wall connections
- Roof geometries
- Wall-foundation connections
- Window air leakage
- Wall-window connections
- Porch/deck attachments
- Mechanical system penetrations
- Rigid air control layer on walls





 EEBA 2011: Massachusetts DER Program: Lessons Learned

Retrofitting Exterior Air Barriers



- Other projects in 1.5 ACH 50 range; ~3-5 ACH 50 outliers, under 1 as well
- Roof-wall connections
- Roof geometries
- Wall-foundation connections
- Window air leakage
- Wall-window connections
- Porch/deck attachments
- Mechanical system penetrations
- Rigid air control layer on walls





 EEBA 2011: Massachusetts DER Program: Lessons Learned


Air Barriers and Brick Buildings

- Pre-retrofit test
- Brick (2-wythe); front and rear exposed, party walls
- Vinyl replacement windows
- Whole-building test
 - 11.7 ACH 50
 - 0.9 CFM 50/sf enclosure
- Roof, chimneys, window-wall interfaces?


 EEBA 2011: Massachusetts DER Program: Lessons Learned

Mechanicals

 EEBA 2011: Massachusetts DER Program: Lessons Learned 65


Mechanical Retrofit

- Range of approaches
- Often similar to new construction
- After enclosure upgrade
 - Much smaller and quieter systems can be chosen
- Air-based can be replaced with hydronic
- Low-temperature (more efficient) systems can be used (e.g., steam → hot water)
- For ventilation load add HRV (or ERV)

 EEBA 2011: Massachusetts DER Program: Lessons Learned 66


Heating: Steam to Hydronic

- Removed hazardous material
- Freed valuable floor space
- More even control
- Efficient, sealed combustion
- Provided option for more efficient water heater



b3c Building Science Corporation EEBA 2011: Massachusetts


Heating: Steam to Hydronic



Manifold Distribution – home run to every radiator

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 68


Heating: Steam to Hydronic



PEX tubing:
Minimally destructive distribution

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 69

Heating: Steam to Hydronic




Thermostatic Radiator Valves (TRVs): every radiator its own zone

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 70

Combustion Safety

- Backdrafting risk in tighter houses
- Combustion air should be drawn from outside (“sealed combustion”)





b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 71

Sealed Combustion

Retrofit atmospherically vented?

- Maybe boilers
- Not water heaters
- Is it worth it?

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned 72

Mini-Splits

Mini-split non-ducted head

Mini-split short ducted system

Mini-split outdoor unit

- Both heating & cooling
- Multi-splits (single outdoor unit)
- Systems with SEER=26 and HSPF=11 available

b3c Building Science Corporation EEBA 2011: Massachusetts

Mini-Splits Heating/Cooling in Cold Climate

- 1818 sf house, solar-oriented, superinsulated (12" spray foam walls, R-80 roof), triple glazed windows, very airtight
- Central Massachusetts location
- Net zero performance

b3c Building Science Corporation

Mini-Split Heat Pumps

Master Bedroom Temperature/RH

Door Sensor

Door Sensor

Temperature/RH (Hall)

Bedroom 1 Temperature/RH (Storage)

Door Sensor

Bedroom 2 Temperature/RH

Mini split head

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned

Mini Split Heating Conclusions

- Single point heating per floor can keep rooms close to setpoint (~5-7° F)
- Deep heating setbacks cause greater differences
- Leaving doors closed increases temperature differences
- Deep setbacks result in long runtimes for mini split heat pumps
- "Acceptable sizing" data inconclusive, but other practitioners in colder climates have hard data
- Effective trade-off for superinsulated enclosure

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned

HRV Induced Flow

- AHU running, HRV not running → unintended airflow
- Overall air leakage + duct leakage issues
- Need motorized damper in addition to backdraft dampers

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned

Site and Source Energy


Electricity: ~20 million Btu/year site energy → ~67 million Btu/year source energy

To make this much electricity ...

...the power plant needs to "burn" this (coal, gas, nuclear ...)

- Site-source conversion changes based on location/grid, time of day, season
- Site-source number has change of improving with more renewable power

b3c Building Science Corporation EEBA 2011: Massachusetts DER Program: Lessons Learned



Questions?

Kohta Ueno
kohta@buildingscience.com

U.S. DEPARTMENT OF ENERGY
Energy Efficiency & Renewable Energy

nationalgrid
THE POWER OF ACTION
www.powerofaction.com/der

EEBA 2011: Massachusetts DER Program: Lessons Learned

80

EEBA Course Description

- **Short Description:**
A New England utility company has implemented a deep energy retrofit pilot program, with the goal of energy savings of over 50%. Several projects have been completed, with several more in progress and under construction. This session will cover measures implemented, savings achieved, and lessons learned in this program.
- **Learning Objectives:**
 - Understand some of the benefits and risks of exterior wall retrofit insulation systems.
 - Understand the pros and cons of including the basement within the conditioned space.
 - Understand some of the challenges involved in retrofitting exterior air barriers to existing buildings.
 - Understand the magnitude of savings achievable with these types of deep energy retrofits.

EEBA 2011: Massachusetts DER Program: Lessons Learned

81