

University of
Waterloo



High Performance Enclosure Details

Dr John Straube, P.Eng.
Dept. of Civil Engineering / School of
Architecture
University of Waterloo
Building Science Corporation

BuildingScience.com



Efficiency Vermont is a Registered Provider with **The American Institute of Architects Continuing Education Systems (AIA/CES)**. Credit(s) earned on completion of this program will be reported to **AIA/CES** for AIA members. Certificates of Completion for both AIA members and non-AIA members are available upon request.

This program is registered with **AIA/CES** for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product.

Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.




Learning Objectives

- *Apply concepts of separating interior and exterior environments to increase enclosure functionality*
- *Choose from various design approaches to create a high performance*
- *Identify design parameters and situations that have been successfully addressed in examples presented*
- *Recommend to clients the advantages and techniques available in designing high-performance enclosures*


The Devil is in the Details

- Targets and codes have raised awareness
- People “know” you need
 - Lots of insulation value
 - No thermal bridges
 - No air leaks
 - A drainage plane leading to flashing
- But, how to this?

www.BuildingScience.com

Basic Functions of the Enclosure

- 1. Support
 - Resist and transfer physical forces from inside and out
- 2. Control
 - Control mass and energy flows
- 3. Finish
 - Interior and exterior surfaces for people
- Distribution – a building function




Functional Layers

Building Science

Basic Enclosure Functions

- **Support**
 - **Resist & transfer physical forces from inside and out**
 - Lateral (wind, earthquake)
 - Gravity (snow, dead, use)
 - Rheological (shrink, swell)
 - Impact, wear, abrasion
- Control
 - Control mass and energy flows
- Finish
 - Interior and exterior surfaces for people




Functional Layers

Building Science Enclosures No. 6 /

Basic Enclosure Functions

- Support
 - Resist & transfer physical forces from inside and out
- **Control**
 - **Control mass and energy flows**
 - **Rain** (and soil moisture)
 - Drainage plane, capillary break, etc.
 - **Air**
 - Continuous air barrier
 - **Heat**
 - Continuous layer of insulation
 - **Vapor**
 - Balance of wetting/drying
- Finish
 - Interior and exterior surfaces for people




Functional Layers

Building Science.com Enclosures No. 7 /

Other Control . . .

- Support
- **Control**
 - **Fire**
 - Penetration
 - Propagation
 - **Sound**
 - Penetration
 - Reflection
 - **Light**
 - Diffuse/glare
 - View
- Finish




Functional Layers

Building Science.com Enclosures No. 8 /

Basic Enclosure Functions

- Support
 - Resist & transfer physical forces from inside and out
- Control
 - Control mass and energy flows
- Finish
 - Interior & exterior surfaces for people
 - Color, speculance
 - Pattern, texture



Building Science.com

History of Control Functions


- Older Buildings
 - One layer does everything
- Newer Building
 - Separate layers,
... separate functions



Building Science.com

No. 10

Changes




Building Science.com

11

The “Perfect Wall”

- Finish of whatever
 - May need ventilated
- **Control continuity is the key**
 - Water: Drainage gap + drainage plane
 - Air: Air barrier
 - Heat: Insulation
 - Vapor: vapor barrier




What is a High-performance enclosure?

- One which provides high levels of control
- Poor *continuity* limits performance
- Poor continuity causes most problems too:
 - E.g. air leakage condensation
 - Rain leakage
 - Surface condensation
 - Cold windows
- This presentation: continuity + high levels

www.BuildingScience.com

Rain Control


- Rain shedding
- Drainage
- Must integrate with flashing, drainholes
- Overlap everything
- No holes



The diagram shows a cross-section of a building wall assembly. From left to right, it consists of cladding (represented by three stacked rectangular blocks), control layers (a vertical blue line), and the structure (a grey block). A blue arrow indicates rain falling from the top left, hitting the cladding. A dashed blue line shows the path of water being directed down and away from the control layers. Labels with arrows point to 'Cladding', 'Control layers', and 'Structure'.

Air Control


- Continuous Air Barrier
 - Continuous
 - Stiff
 - Strong
 - Durable
 - Air Impermeable
- Only very small holes tolerable







The diagram shows a cross-section of a building wall assembly. From left to right, it consists of cladding (represented by three stacked rectangular blocks), control layers (a vertical blue line), and the structure (a grey block). A solid green vertical line runs through the control layers, representing the air barrier. Labels with arrows point to 'Cladding', 'Control layers', and 'Structure'.





Heat Control





- Continuous Thermal Barrier
 - Even R10 is good
- Accept small penetrations as long as no comfort or durability issues
- Windows are a major concern
 - Heat loss/gain
 - Solar gain





The diagram shows a cross-section of a building wall assembly. From left to right, it consists of cladding (represented by three stacked rectangular blocks), control layers (a vertical blue line), and the structure (a grey block). A solid red vertical line runs through the control layers, representing the thermal barrier. Labels with arrows point to 'Cladding', 'Control layers', and 'Structure'.










Enclosure Design: Details

- Details demand the same approach as the enclosure.
- Scaled drawings required at 

Details needed at:

- Change in *plane*
- Change in *material*
- Change in *trade*











A 3D cutaway diagram of a building's structural frame, showing multiple levels of floors and columns. Red circles are placed at various points where different materials, planes, or trades meet, indicating locations where detailed design is required. The diagram is labeled 'Building Science.com' and '31/175'.



Details

- Need to trace continuity of
 - Structure (connections)
 - Water control
 - Air Control
 - Thermal control

www.BuildingScience.com








Windows

- Finding the air-water-thermal layer can be challenging
- Usually, best air and water seal is inner edge
 - few chances for water leaks at corners
- Alu windows have thermal line at TB
 - Line up with thermal control in wall

www.BuildingScience.com

Leaky windows

- Studs and sheathing are sensitive to leaks






Mixed membrane + liquid







Backdams / Slopes are Important




















Continuous interior angle provides backdam and airseal continuity







Basement Wall-Slab

- Continuity of air-thermal barrier a challenge at slab
- Continuity at floor slab also!

