

Vancouver Field Exposure Facility: Phase III Construction and Instrumentation Report

Research Report - 1304

May 2010 (posted April 2013)

Aaron Grin and Jonathan Smegal

Abstract:

This report describes the construction and instrumentation of Phase III of a multi-phase, multi-year research project at the Vancouver Field Exposure Test Facility in Coquitlam, British Columbia. Phase III focusses on the performance of various sheathings and claddings in a high stress moisture environment that is typical of the Pacific Northwest climate. The main research goal is to examine the performance of the various walls under the influence of intentional exterior wetting events in the drainage space..

VANCOUVER FIELD EXPOSURE FACILITY

Phase III Construction and Instrumentation Report

May 14th, 2010 (posted April 2013)

Prepared by



Aaron Grin PEng, MASc
Jonathan Smegal MASc

Building Science Corporation
30 Forest Street
Somerville, MA 02143
United States

167 Lexington Court, Unit 5
Waterloo, Ontario
Canada N2J 4R9

www.buildingscience.com

Introduction

This multi-phase, multi-year research project at the Vancouver Field Exposure Test Facility in Coquitlam, British Columbia is led by Building Science Corporation (BSC) and Gauvin 2000 Construction Limited. This report describes the construction and instrumentation of Phase III of the research project¹.

Phase III will demonstrate the performance of various sheathings and claddings in a high stress moisture environment that is typical of the Pacific Northwest climate. The main research goal is to examine the performance of the various walls under the influence of exterior intentional wetting events in the drainage space. The wall of specific interest is constructed with extruded polystyrene sheathing. As part of this multi-year test program, walls were subjected to normal interior and exterior stresses during the first year, high internal stress in the second year, and will see high external stress in the third year. The expected final deliverable will be a research report prepared at the conclusion of the Phase III testing².

Background: Vancouver Field Exposure Facility

The test facility was constructed in the fall of 2005, in Coquitlam, British Columbia. The hut permits the side-by-side construction and comparison of seven 4'x8' (1.2m x 2.4m) test wall panels on each cardinal orientation for a total of 28 wall test panels and three 12' x 24' (3.6m x 7.2m) roof panels on the north and south facing roof slopes for a total of six roof test panels. All of the test panels are exposed to the same indoor conditions. The objective of the initial test program was to determine the performance of historical, current and possible future wall assembly configurations under field conditions.

¹ This report was written prior to the completion of Phase III, which ran from December 17, 2009 to November 3, 2011. It is provided for reference. For current information about the Vancouver Test Hut Project, see www.buildingscience.com/documents/special/vancouver-test-hut.

² Smegal et al, RR-1207: Vancouver Field Exposure Facility: Phase III Exterior Insulation Analysis, available at www.buildingscience.com/documents/reports/rr-1207-vancouver-field-exposure-facility.




Figure 1 - Test Facility Location in Coquitlam, British Columbia



Figure 2 – Test Facility and Immediate Surroundings

The test facility was constructed on the roof of a low-rise office building, which is owned by Gauvin 2000 Construction (a British Columbia builder who is a co-sponsor of this research project). This eliminated the need to buy or rent a large empty site (with free wind approach) in the expensive real estate market of greater Vancouver. It also affords the test facility some protection from potential vandals. Figure 3 and Figure 4 show elevation drawings of the test facility.




Figure 3 - North & South Elevation




Figure 4 - East & West Elevation

A steel mast on the roof of the test facility supports a weather station at a height of 22 ft (6.7 m) above the roof of the office building and 50 ft (15.2 m) above ground level. The monitoring system continuously collects weather data including temperature, relative humidity, wind speed and direction, rain, and solar energy.

Phase III Construction and Instrumentation

This is the third phase of testing completed at the Coquitlam test facility. The Phase II walls were deconstructed and removed to ensure that the effects from Phase II testing do not affect Phase III testing and observations. This phase will utilize wetting apparatuses on both the interior and the exterior of the exterior wood sheathing. The Phase III walls were built and installed by Gauvin 2000 Construction and instrumented by BSC staff during the week of November 2nd, 2009. Installation of the insulation and finishes continued until late November and the final programming was completed by BSC in early December.

Table 1 lists the test walls along with the materials used. Some of the wall test panel assemblies were chosen to represent conventional construction practices from the past 40 years while others are designed to investigate the role of specific layers, and to test possible products and systems.

Table 1 - Wall Construction Details

		Frame	Interior Finish	Vapour/Air Barrier	Thermal Insulation	Exterior Sheathing	Air/Weather Barriers	Exterior Cladding (System)
		2x4 2x6	1/2" drywall + paint	kraft paper w/ tabs 6 mil poly (sealed) latex paint	R-8 fiberglass batt R-20 friction fit batt	3/8" plywood 1/2" OSB 1/2" OSB + 1 1/2" DOW XPS	1 layer 30 minute paper Tyvek Tyvek Drain Wrap under Lathe Paper 2 layers 30 minute paper Tyvek Drain Wrap on OSB Lathe Paper on XPS	Stucco (3/4") 3/4" cavity (vert. wood strapping) Asphalt Backer Board Stucco (3/4") 3/4" cavity (vert. wood strapping) Hardie Plank (back primed) 3/8" drainage gap (Dow Farnfold) Hardie Plank (not back primed)
East & West Wall Panel Assemblies	Panel 1 Early - 2x4 (R-8 paper-back batt)	•	•	•	•	•	•	•
	Panel 2 Energy Efficient - 2x6 (air-tight 6 mil poly)	•	•	•	•	•	•	•
	Panel 3 Energy Efficient - 2x6 (no poly)	•	•		•	•	•	•
	Panel 4 Energy Efficient - 2x6 (no poly / housewrap)	•	•		•	•	•	•
	Panel 5 Rainscreen - 2x6 (6 mil poly / 3/4" rainscreen)	•	•	•	•	•	•	•
	Panel 6 Rainscreen - 2x6 (no poly / 3/4" rainscreen)	•	•	•	•	•	•	•
	Panel 7 Exterior Insulation - 2x6 (no poly / insul. sheathing)	•	•		•	•	•	•
North & South Wall Panel Assemblies	Panel 1 Early - 2x4 (R-8 paper-back batt)	•	•	•	•	•	•	•
	Panel 2 Energy Efficient - 2x6 (air-tight 6 mil poly)	•	•	•	•	•	•	•
	Panel 3 Energy Efficient - 2x6 (no poly)	•	•	•	•	•	•	•
	Panel 4 Energy Efficient - 2x6 (no poly / housewrap)	•	•	•	•	•	•	•
	Panel 8 Hardie Strapped - poly (poly / 3/8" rainscreen)	•	•	•	•	•	•	•
	Panel 9 Hardie Strapped - no poly (no poly / 3/8" rainscreen)	•	•	•	•	•	•	•
	Panel 7 Exterior Insulation - 2x6 (no poly / insul. sheathing)	•	•	•	•	•	•	•

Each of the test walls was outfitted with a series of temperature (T), relative humidity (RH) and wood moisture content (MC) sensors. These sensors will continuously monitor and record to the data acquisition system throughout the testing period. All walls received a similar sensor package. This package is illustrated in Figure 5.




Figure 5 - Typical Instrumentation Package

Moisture content pins were installed in the framing lumber and the sheathing in all wall systems. Wood moisture contents can be determined from the electrical resistance of wood based on the Garrahan equation. These pins can be used to measure moisture content at any depth because the pins are electrically insulated except for the tip. Measurements are most commonly taken at 1/4" or 6mm in depth. With the exterior wetting systems introduced in Phase II, a double set of moisture pins were used. One set was at the standard depth to measure the MC of the interior face of the sheathing and one set was set deep to measure the exterior face MC of the sheathing. The wood moisture content pins were installed in combination with a temperature sensor in all locations. The temperature sensor was drilled to the depth of the moisture content pins and the temperature readings are used to correct the wood moisture content readings.

Relative humidity sensors were always installed in combination with temperature sensors, both of which were protected by a vapor permeable, water resistant cover. Relative humidity and temperature sensors were installed at the midpoint of the stud space, between the drywall and the sheathing, behind the drainage material at two heights and outboard of the drainage material at mid-height.

Example photographs of the individual sensors are shown below in Figure 6 to Figure 11.




Figure 6 - Interior and Exterior Sheathing MC/T Sensors



Figure 7 - Upper Interior Sheathing MC/T Sensors



Figure 8 - Interior Mid-Height T, T/RH and MC/T sensors



Figure 9 - Bottom Plate MC/T Sensors




Figure 10 - Exterior Mid-Height T/RH Sensor Outboard of Building Paper



Figure 11 - Exterior Upper and Lower T/RH Sensors



Figure 12 - Installation of Dow XPS 1.5" Insulation

Figure 12 shows the installation of the 1.5" exterior XPS over housewrap. A small pocket approximately 3/8" (10 mm) wide and 1/4" (6 mm) deep was cut out of the back of the XPS to allow the T/RH sensor and wire to fit behind the XPS and not create a gap between the XPS and the housewrap. The pocket is shown in more detail in Figure 13.



Figure 13 - Sensor Pocket in XPS Insulation

For Phase III, wetting systems were installed on both the interior and the exterior of the exterior sheathing to allow a known amount of water to be injected at a controlled time and location. The wetting apparatus consists of a storage media and a tube connecting the storage media to the interior of the test hut to enable wetting without opening the wall system. The wetting system was designed to simulate a window leak, and was used to help determine the drying potential of specific wall assemblies. Photographs of the installed wetting systems are shown in Figure 14 to Figure 16.



Figure 14 - Exterior Wetting Apparatus



Figure 15 - Interior Wetting Apparatus



Figure 16 - Wetting Apparatus Injection Tubes

Upon completion of the sensor installation, the stud space insulation and interior and exterior finishes were applied by Gauvin 2000 Construction sub-contractors. These tasks took approximately three weeks to complete. Figure 17 and Figure 18 show a few of the final phases of construction.



Figure 17 - Interior Vapor Control and Stud Space Insulation



Figure 18 - Stucco Base Coat and Mid-Height T Sensor

Construction was completed by late November and the final data acquisition system programming and connection was completed in early December. Official data collection began December 17th, 2009.

Data Acquisition System

The data acquisition system consists of the following:

- One Campbell Scientific Power Supply
- One Campbell Scientific Network Link Interface
- Two Campbell Scientific Data Loggers
- Ten Campbell Scientific Multiplexers
- 1 Weather Station
- 3 Indoor Conditions Relative Humidity and Temperature Sensors
- 2 Rain Gauges
- 56 Test Specimen Temperature Sensors
- 112 Test Specimen Relative Humidity and Temperature Sensors
- 168 Test Specimen Moisture Content and Temperature Sensors

This Campbell Scientific system allows accurate, remote monitoring of the entire system from anywhere with internet access. Each of the temperature sensors was manually tested during the initial installation to verify that they were functioning. The moisture content and relative humidity sensors were tested to verify functionality using the data acquisition system.

Planned Milestones and Reporting

Preliminary data shows that the walls have not dried sufficiently to begin wetting events. Once the walls have dried, wetting events will be planned appropriately to coincide with natural wetting events. The expected final deliverable will be a research report prepared at the conclusion of the Phase III testing³.

³ Smegal et al, RR-1207: Vancouver Field Exposure Facility: Phase III Exterior Insulation Analysis, available at www.buildingscience.com/documents/reports/rr-1207-vancouver-field-exposure-facility.

About the Authors

Aaron Grin is a building scientist and researcher with a background in structural Civil Engineering.

Jonathan Smegal's work at BSC includes laboratory research, hygro-thermal modeling, field monitoring of wall performance, and forensic analysis of building failures.

Direct all correspondence to: Building Science Corporation, 30 Forest Street, Somerville, MA 02143.

Limits of Liability and Disclaimer of Warranty:

Building Science documents are intended for professionals. The author and the publisher of this article have used their best efforts to provide accurate and authoritative information in regard to the subject matter covered. The author and publisher make no warranty of any kind, expressed or implied, with regard to the information contained in this article.

The information presented in this article must be used with care by professionals who understand the implications of what they are doing. If professional advice or other expert assistance is required, the services of a competent professional shall be sought. The author and publisher shall not be liable in the event of incidental or consequential damages in connection with, or arising from, the use of the information contained within this Building Science document.