
Summer Camp XXVII 2025





Using AeroBarrier in Existing Multifamily and Existing Homes



Mike Lubliner, CARES Dave Bohac, CEE

Twenty-Seventh Westford Symposium on Building Science



AeroBarrier Case Studies
Weatherization & "Gut Rehabs"
Low-Rise Multifamily
Dwellings Opportunities In
Existing Public Housing

Mike Lubliner CARES



Dan Auer & Jesse Bennett King County Housing Authority





Exterior AeroBarrier: Air Sealing Attics and Crawlspaces of Occupied Residences

Dave Bohac
Center for Energy & Environment



Weatherization & "Gut Rehabs" Low-Rise Multifamily Dwellings

Acknowledgements

- Mike Lyons & Mark Modera Aeroseal™
- Dave Bohac Center for Energy and Environment
- Collin Olson The Energy Conservatory
- Chase Davis Obrien 360
- Chase Counts Arrow Insulation
- Andre Dejarlais -Oak Ridge National Laboratory
- Joe & Betsy Building Science Corporation



Weatherization & "Gut Rehabs" Low-Rise Multifamily Dwellings

King County Housing Authority

KCHA is a key leader in affordable public/private housing partnerships with; Puget Sound Energy, Washington State Department of Commerce, Bonneville Power Administration, Northwest Energy Efficiency Alliance, with state & national support!

- Washington's largest landlord https://www.kcha.org/
- Affordable rental housing & assistance to more than 50,000 people
- Low-rise multi-family are "woody walkups/corridor 50%/50%"
- Typical individual mechanical & utility metering
- Deep energy retrofits in LRMF, SF & buys/operates MH "parks"






Windsor Heights Seattle



Gut Rehab "car decking" over vented crawlspace







Windsor Hts: Gut Rehab "car decking" over vented crawlspace


Results With & Without AeroBarrier

- Old "rat-piss and falling down" R-19 batt insulation removed (W&V)
- All crawlspace vents were sealed & BD used to pressurize crawl (V)
- AeroBarrier was injected Building V crawlspace
- All crawlspace vents were then unsealed (V)
- New R-30 floor batts installed (V)
- No AeroBarrier for Building W

Building	# Units	Test In Date	Test In	Test Out Date	Test Out	Reduction
V	10	9/19/2016	5774	11/20/2019	3203	<mark>44.53%</mark>
W	10	9/19/2016	5123	11/20/2019	3899	<mark>23.89%</mark>


Windsor Hts: Whole building exterior envelope leakage test results (TECLOG 4)

Building W: Without AeroBarrier



Windsor Hts: Whole building exterior envelope leakage test results (TECLOG 4)

Building V: With AeroBarrier



Evergreen Terrace Renton WA

Gut Rehab "car decking" over vented attic





Total Leakage Reduction 20 ACH50 to under 2 ACH50



Renton: Gut Rehab "car decking" over vented attic

Results

- 14 buildings, 50 units, 1963's w/upgrades
- AeroBarrier pressurized injection "unit by unit" each unit to seal; attic and walls
- Un-insulated slab on grade
- Attic loose fill R19 R49
- Build tight ventilate RIGHT Ducted HRV
- Ductless Heat Pumps Got AC!





Renton: Gut Rehab "car decking" over vented attic

AeroBarrier Reports



ENVELOPE SEALING REPORT

Envelope Sealing Performed For: King County, Housing Authoritty 3030 B NE 15th St, WA 98056 AEROBARRIER CASE ID: 8013 HARDWARE: AeroBarrier DATE: **BUILDING TYPE:** 6/5/2020 **Envelope Sealing Results: Envelope Sealing Progress:** BEFORE SERVICE 16001 1435.3 CFM of Leakage, equivalent to a 172.8 Square Inch Hole or 20.40 Air Changes per Hour 1200 (for your 508 square-foot structure inclosing a volume of 4221 cubic feet 1000 AFTER SERVICE 133.3 CFM of Leakage, equivalent to a 800 16.0 Square Inch Hole or 1.89 Air Changes per Hour This corresponds to a 90.7% Reduction in Envelope Leakage NOTE: Envelope leakage and air-change results are 20 40 60 80 100 120 140 calculated at a standard pressure of 50 Pa. Sealing Time in Minutes **Envelope Sealing Performed By:** Ekovate Air, LLC 502 Rainier Ave S Suite 206 Seattle, WA 98144 Phone: (206) 491-7111

DATE: BUILDING TYPE: Apartment

Envelope Sealing Results:

BEFORE SERVICE

686.2 CFM of Leakage, equivalent to a 82.6 Square Inch Hole or 11.93 Air Changes per Hour


(for your 370 square-foot structure enclosing a volume of 3452 cubic feet)

AFTER SERVICE

68.8 CFM of Leakage, equivalent to a 8.3 Square Inch Hole or 1.20 Air Changes per Hour

This corresponds to a 90.0% Reduction in Envelope Leakage

NOTE: Envelope leakage and air-change results are calculated at a standard pressure of 50 Pa.



Kirkland Heights Kirkland

New Construction w/100% AeroBarrier (woody walkup)








Results

- 27 buildings, 325 units, 80% completed
- Slab on grade, three-stories
- Non guarded test (total leakage) w/windows open in adjacent units
- Built to WA WSEC "tighter with HRV energy credits" for compliance w/ER heat
- CO2 central HPWH New emerging technology (Ecotope – Mechanical-DHW)
- HRV in each unit to each room, ER heat, No Cooling
- PV on site





Results



The units in the newly constructed buildings averaged 27% below the 0.25 CFM50/sf target





Results

Building 10 example

June 12-14, 2024
All units passed WSEC Option

Target: 0.25 CMF50/sf (unit SA)

521 cfm50 vs. 698 cfm50 Average 25% below code

Unit	Test Results (CFM ₅₀) Depressurization	Single-Point Test Results (110% Result)	R406.3, Option 2.2 Target (0.25 CFM ₅₀ /ggft)	Unit Enclosure Area (satt)	Unit Conditioned Floor Area (satt)
10 A	336	370	648	2,590	785
10 B	431	474	748	2.990	926
10 C	546	601	748	2,990	926
10 D	355	391	648	2,590	785
10 E	339	373	648	2,590	785
10 F	460	506	748	2,990	926
10 G	508	559	748	2,990	926
10 H	374	411	648	2,590	785
10 I	555	611	648	2,590	785
10 J	602	662	748	2,990	926
10 K	642	706	748	2,990	926
10 L	530	583	648	2,590	785





Results

- Arrow bid \$1.85/sq ft to remove batt insulation in an attic.
- Arrow bid \$1.60/sq ft to remove loose fill insulation in an attic.
- Air seal specifications requires air sealing all joints in the attic floor:
- Air seal attic w/existing insulation = \$0.60 \$0.65/sq ft
- Air seal attic w/o insulation = \$0.55 \$0.60/sq ft

\$2.15 - \$2.50/sq ft - Remove old and air seal w/o AB





Future Research?

Deep energy retrofits case studies at gut-rehab:

- Conduct Survey to Identify Stakeholder Value Proposition(s)
- Conduct (SIR) Cost/Benefits Parametric Analysis

Research to Assess:

Tenant, building owners, contractors, utilities & WX crews, KCHA contactors feedback:

- Odor Control
- Sound Control
- Thermal Comfort
- Indoor Air Quality
- Utility Bills impacts (energy and demand)
- Savings to Investment Ratio
- Other Non-energy Benefits

Your thoughts are appreciated!



Dwellings Resilience Improvements

- Air sealing "big-leaks", Blower door guided pre/post whole building and each unit tests
- Dense-pack 2x4 walls, added to existing R2- R11 to R15 (insulates & air seals)
- Continuous wall insulation often added when re-siding
- Energy Star or better; window, door, appliances, lighting replacements
- Vented attic old insulation removed or moved & air seal big holes, insulate to R38-49
- Vented crawl floor insulation moved & air seal, & replaced, insulate to R30-38
- Insulating uninsulated slab at grade at perimeter
- Replace HVAC electric/gas heaters with DHP's & EPCHOA "DDPTAC"
- Upgraded ventilation system to 62.2 and install H/ERV's, if & when appropriate
- Upgraded electric/gas DHW to Heat Pump Water Heaters when appropriate
- PV on roof when reroofing and appropriate






Where are the leaks that are bigger than the other leaks? Right-On!

Deep energy retrofits case studies at gut-rehab:

- Chat with Dan & Jesse
- Chat with Dave & Luby
- Chat with Dr. Mark Modera & Emily

Build tight & ventilate right!





AeroBarrier Case Studies
Weatherization & "Gut Rehabs"
Low-Rise Multifamily
Dwellings Opportunities In
Existing Public Housing

Mike Lubliner CARES

Dan Auer & Jesse Bennett King County Housing Authority



Exterior AeroBarrier: Air Sealing Attics and Crawlspaces of Occupied Residences

Dave Bohac Center for Energy & Environment











Exterior AeroBarrier: Air Sealing Attics and Crawlspaces of Occupied Residences

Acknowledgements



Mike Lyon
Lead Application Engineer
Aeroseal






Curtis Harrington
Co-Director of Engineering
UC Davis, WCEC






Traditional Inside – Out Method



New Exterior Outside – In Method



Equipment Development - ongoing

AeroBarrier Select





Attic Sealing Process

- Less invasive
- No surface preparation required
- Requires removal of attic insulation
- Depressurize living space while injecting in attic
- Occupants leave for ~1-2 hours





DOE BENEFIT Project

Test process in a realistic product delivery environment in SF & MF homes and evaluate; field performance, experience needed to refine the process and validate the value proposition to stakeholders. Research tasks include:

- Stakeholder outreach (HROME meeting etc.)
- Market structure scenaros research
- Identify barriers/opportunities in (WAP) & (HPC) for low-income clients
- Energy/economic Savings to Investment Ratio (SIR) analysis
- Inform moisture durability, and (IAQ) non energy benefits.



CalNEXT Demonstration Project

Goal – Develop and demonstrate less invasive approach for aerosol sealing of existing homes

- Adapt existing aerosol sealing methods to address occupied homes
- Measure performance of sealing approach in different building types
- Develop and document installation protocols
- Provide recommendations for sealing equipment



Curtis Harrington
Co-Director of Engineering
UC Davis, WCEC





CalNEXT Demonstration Project

5 single-family

- 1 attic only
- 2 crawlspace only
- 2 attic and crawlspace

11 multifamily

all 11 attic only


Compare to other sealing methods

- Manual applied canned foam
- Spray-on elastomeric





Single Family Homes



Vintage: 1900-1972

Size: 1,191-2,491 ft2

Starting leakage:

3-18.6 ACH50



Exterior AeroBarrier: Single Family Homes

Site 1

- Early 1900s, gut rehab, 1,420 sf
- Crawlspace sealing only (conditioned attic)
- 3.0 >> 1.9 ACH50 (38%)
- 87% of 283 CFM50 CS to house leakage was sealed







Exterior AeroBarrier: Single Family Homes

Site 4

- 1961, 2-story, 2,491 sf
- Partial crawlspace and slab-on-grade
- Crawlspace sealing only difficult attic insulation removal
- 10.0 >> 9.1 ACH50 (3%)
- 60F and raining (100% RH), depressurization ~ 70Pa
- Opened a patio door to reduce sealing in living space





Exterior AeroBarrier: Single Family Homes


Site 5

- 1972, 1-story, 2,136 sf
- Attic sealing only, ducts in attic
- 12.7 >> 8.5 >> 4.2 ACH50 (49%)
- sealed 133 CFM25 or 34% of the total duct leakage
- Sealing occurred at exposed joints, better sealing w/removed insulation





First Multifamily Sealing










Sealed 3 apartments with each of the methods

Compare to Manual Methods



Elastomeric




Hand Foam



4 AeroBarrier Only and 4 Manual + AeroBarrier

8 Multifamily Sites – Attic Sealing





Sample Seals













Barriers to Adoption

- Requires removal of insulation
- Manually seal gaps > 3/8"
- Requires tenants to leave for 1-2 hours
- Higher cost than manual sealing
- Still on the pathway to commercialization



Opportunity

- Air sealing responsible for single largest natural gas reductions in WAP (20% - 30%)
- Outperforms conventional attic air sealing
 - 42% SF average leakage reduction (37% 49%)
 - 39% MF average leakage reduction (32% 50%)
 - Manual: 14% can foam, 26% elastomeric
- Greater reduction with other WX measures
- Little or no prep to occupied space
- Process can seal ducts at the same time
- New equipment > save labor and reduce invasiveness






















THANK YOU

dbohac@mncee.org

mike@lubycares.com