

Engineered Wood is Better? But Also Stranger...

The Cast of Characters



CLT



GLULAM



NLT



DLT



LVL



LSL



PSL



MPP



Cross Laminated Timber (CLT)



11

Not All CLT Quality is the Same



Structural non-finish grade
(Canadian product)



High quality interior finish
grade (European product)



Custom clear finish interior tongue &
groove with wood dowels (Canadian)



12

Glulam & Glue Laminated Timber (GLT) Panels



13

Nail Laminated Timber (NLT)



14

Many Historical Examples - Heavy Timber Framing with NLT Floors



15

Dowel Laminated Lumber (DLT)



16

Laminated Strand Lumber (LSL) & Parallel Strand Lumber (PSL)



17

Laminated Veneer Lumber (LVL)



18

Mass Plywood Panel (MPP)



Mass Timber is Beyond Stick Framing



It Borrows a Lot from Heavy Timber Framing



And Borrows a Bit from Pre-Cast & Tilt-Up Concrete



22

And Combines Pre-fabrication Modular & Panelization




Will Always Utilize Concrete & Steel Components



24

And Use Wood Where Wood Makes Sense



25

Post & Beam



Post & Beam



Post & Plate (Panels)



Solid Wood Panels



Origine - Nordic Structures

29

What Makes Mass Timber Buildings Unique?

- Use of engineered mass timber components
 - Alternate structural systems (post/beam, engineered panels, infill components)
 - Unique & new connections, interfaces & details
 - Hybrid steel-wood-concrete components & connections
- Longer & heightened exposure of large wood components to rain and weathering during construction
- *Is not the same as stick built mid-rise wood-frame, but is also different from high-rise steel or concrete structures*



Why Taller Wood - Why Now?

- Building codes are rapidly changing to allow both larger and taller wood buildings across North America
 - 5&6 storey wood-frame (stick-built) now allowed in many N.A. jurisdictions
 - Even taller & larger mass timber buildings being constructed as alternate code solutions (Canada and the US)
 - Many precedents in Europe and AUS/NZ
- Significant research, testing, and current interest in taller wood buildings
- Wood seen as a sustainable and renewable resource with bonus carbon storage
- Cost & speed of construction benefits?



1900s era Tall Wood Buildings Across North America



2016 - UBC Brock Commons, Student Residence - Currently the Tallest Wood Building in the World, 18 storeys, 53m



The Carbon Argument for More Wood in Buildings

- **Operating Carbon**
 - Carbon equivalent emitted as part of operation and maintenance
 - Reduced with *energy efficiency measures*
- **Embodied Carbon**
 - Cumulative equivalent emitted carbon from acquisition, manufacture, transport, and installation of material
 - Reduced with *low carbon or carbon sequestering materials*
- **Trend** - In jurisdictions with low carbon energy grids and energy efficient building standards - embodied carbon really starts to become important (i.e. the likely future)



The Carbon Argument for Tall Wood Buildings

Natural reg and plantir begin the c



ESTIMATED ENVIRONMENTAL IMPACT OF WOOD USE

- V** Volume of wood products used: 2,233 cubic meters of CLT and Glulam
- T** U.S. and Canadian forests grow this much wood in: 6 minutes
- C** Carbon stored in the wood: 1,753 metric tons of CO₂
- G** Avoided greenhouse gas emissions: 679 metric tons of CO₂
- ✓** Total potential carbon benefit: 2,432 metric tons of CO₂

THE ABOVE GHG EMISSIONS ARE EQUIVALENT TO:

- 🚗** 511 cars off the road for a year
- 🏠** Energy to operate a home for 222 years

storage plateaus prests and can : released as ay or burn




Gradual release CO₂


Wood build and it rem: the lifetim

*Estimated by the Wood Carbon Calculator for Buildings, based on research by Setfrie, R. and J. O'Connor, 2010, A Synthesis of Research on Wood Products and Greenhouse Gas Impacts, FPInnovations (this relates to carbon stored and avoided GHG).
*CO₂ in this case study refers to CO₂ equivalent

ig for wood ensures that intinues to 33



Challenges: Fire Code Solutions - Encapsulation




35

Challenges: Fire Code Solutions - Charring




Challenges: Structural Solutions



37

Challenges: Structural Movement?



Wood Innovation Design Centre - 6 tall storeys, ~98'

Michael Green Architecture (MGA)

38


Wood Movement at WIDC – Monitored & Measured

- Overall building height
~98 ft – continuous glulam columns/CLT core walls with glulam beams/CLT floor panels
- Glulam columns 6 tall floors – total ~ ½” (0.04%) longitudinal shrinkage/compression
- CLT core walls 6 tall floors – total ~ ¾” (0.06%) longitudinal shrinkage/compression
- 5 ply CLT floor panels (6.5”) ~3/16” shrinkage in thickness (3%) each floor – **but separate from load path**



Initial wood moisture content of 14% dried down to a low of ~ 4%

Many Precedents – Europe, Australia & North America



Next World's Tallest Wood Building – HoHo, Vienna




Rüdiger
Lainer +
Partner **RLP**

A few of Our Past & Current Mass Timber Projects



RDH BUILDING
SCIENCE



Mass Timber Integrated into Building Enclosures

- Mass timber elements often a part of the building enclosure
 - Above Grade Walls & Roofs
 - Wood or parts of wood desired to be left exposed - serves both functional and aesthetic purpose
 - Requires protection from moisture during construction & in-service
 - Assemblies with wood, membranes, insulation, accessories control heat, air, and moisture transfer along with noise and fire
 - Designed to accommodate building movement, structural loads, initial & seasonal wood movement




45

Taller Wood Building Structures

- Potentially fast
- Sensitive to moisture
- Greater movement (shrinkage & drift)
- Fire code challenges
- Mixed steel, concrete & wood components & connections



Building Enclosures for Mass Timber Structures



- **Tall Structures**
 - More repetitive, more exposed, need for more speed - *ideal for prefabrication*
 - Less focus on roof and more on walls for weather protection
- **Low-rise structures**
 - Less repetitive? Less exposed
 - Greater focus on roof for weather protection than walls




47

Tall Wood Building Enclosures

- **Need for Speed**
 - Erect and seal as fast as possible to protect the wood structure
 - Preference for offsite prefabrication & minimal site preparation
 - Be accommodating of inclement weather
- **Ensure Durability**
 - Robust materials - high-rise appropriate
 - Be more tolerant of movement
 - Thermally efficient
 - Non-combustible




Facades for Tall Wood Buildings?



49

Load Bearing versus Hung "Curtain-wood" Exterior Enclosure Walls



Good vs Bad Use of Mass Timber




Good - Warm, dry and protected by the building enclosure ☺

Bad - exposed to weathering ☹



51



CLT Wall Considerations




Best Placement & Insulation Type? - It Depends!



52




CLT Panel Interface Air Tightness?



RDH BUILDING SCIENCE

55


CLT Interface Air Barrier Detailing Considerations




RDH BUILDING SCIENCE

56


Air Barrier/WRB Membranes for CLT Panels



Roofs - Exterior Insulated (Conventional or PMR)




CLT Roof Considerations





59

Venting Above Mass Timber Panels in Roofs



60






UBC Tall Wood Structure – Prefabricated & Fast




UBC Tall Wood House - Façade Challenge




65

UBC Tall Wood House - Façade Design Criteria




66


Façade Prefabrication - Small Panel with Separate Windows







Façade Prefabrication - Large Panel with Pre-installed Windows



UBC Tall Wood - Prefabricated Panel Competition












Site Installation







CLT is Not Airtight - Don't Forget the Membrane




CLT is Not Airtight - Don't Forget the Membrane




RDH BUILDING SCIENCE


81



NLT Panel Shrinkage Considerations



Lamination expansion due to swelling



Lamination position after NLT has returned to lower moisture






83

NLT Considerations - Design for Movement





The Biggest Challenge with NLT Overhangs




85

NLT Panel Air Sealing in Factory




Plan



Section



The Biggest Challenge - Managing Water Effectively During Construction



RDH BUILDING SCIENCE

87

Keep Wood Dry & Use Appropriate Materials in Contact with Damp Wood



88

**Take Care with Impermeable Roof Membranes –
Can Be Double Edged Sword**



Protect NLT from Excessive Wetting But Not Too Late



90

...Or Just Plan Ahead & Take Advantage of the Protection



Finland - use of climbing roof and overhead cranes - high degree of modular moisture sensitive components

Mass Timber Can Be Dried Out... Albeit Slowly



92

Protection of Mass Timber Panels During Construction

- Pre-applied torch applied roofing membranes applied to horizontal panels in factory
- Laps torched onsite immediately after installation



93

Lots of Protection Options for Mass Timber Panels During Construction



Wetted NLT Panels Can Move a Lot!



RDH BUILDING SCIENCE

Swelling Wood Is an Almost Unstoppable Force



Pick the Right Wood Product for the Application



97

Know the Wood You Are Using



98

CLT Is Not Watertight During Construction



RDH BUILDING SCIENCE

99

Try to Avoid Drywall Until You Have A Roof or Water-tight Floor Overhead



100

Sanding & Site Finishing Is Often Required




Protection of CLT During Construction



End grain is very absorptive

Water repellants can help reduce uptake into wood


5 ply CLT - ½ Untreated & ½ Treated with water repellent



Splits, checks & joints that allow water past top layer can be problematic

Erect & roof as fast as possible to protect from rain to avoid delays

A Little Protection Goes a Long Way




But the Wrong Protection Can be A Mess..



Coating Lessons - CLT


- Primary purpose for temporary moisture protection to reduce wetting to avoid drying and keep construction on schedule
- Factory Coatings
 - CLT end grain/panel edge coatings are effective
 - CLT surface coatings are useful though not always needed
- CLT will benefit with a coating below wet concrete floor toppings



105

Key Takeaway - Have a Moisture Management Plan

- Step 1: Risk Evaluation - Consider Climate, Rainfall, Construction Schedule, Length of exposure of all mass timber floors/roof etc.
- Step 2: Factory applied coatings
- Step 3: Pre-applied or field applied temporary or permanent membrane protection?
- Step 4: Active water management team onsite to reduce uptake (small tarps, squeegees/vacuums etc.)
- Step 5: Whole building tarping & protection systems
- Step 6: Environmental drying
- Step 7: Mechanical drying contingency



The Future of Tall Wood Facades/Enclosures

- Facades/enclosures erected at same pace as structural systems for tall wood buildings
- Growing local market opportunities for various prefabricated wall & window assemblies
 - Will see a combination of steel, concrete, wood framing or wood panel structural systems used
 - Systems will borrow technology from precast concrete and aluminum curtainwall industry, evolve and adapt for mass timber structures
 - Use of hung “curtainwall” facades instead of load-bearing exterior walls



Discussion & Questions

Graham Finch - gfinch@rdh.com - 250-479-1110

