building science.com

© 2008 Building Science Press

All rights of reproduction in any form reserved.

The SNAPSHOT Form

Building America Report – 0413b

2004

Building Science Corporation

Abstract:

SNAPSHOT stands for Short, Non-destructive Approach to Provide Significant House Operation Thresholds. It is a test form used in the Building America program to ascertain house performance and specifications.

		SNAPSH	$OT^{oldsymbol{0}}$ "The Form	1 "		
Lot #:	: Subdivision:		Address:		Date and time:	
Model	:					
INIII	IALIZATION Square foot				T	ca ft
	Square feet Surface area (all outside surfaces including foundation)				sq. ft.	
	Surface area (all outside surfaces, including foundation) Volume				sq. ft. cu. ft.	
	Windspeed (approximate mph)				mph	
	Outside temperature (estimated)					 ° F
	Check that all registers and bedroom doors are open.				Yes No	
	Measure static pressure in return between fan & filter.				pa	
	Static pressure in Supply and Return				S Pa/	
	Is there a ventilation system?				_	No No
	Type of ventilation system (e.g., exhaust-only, HRV, ERV)				103	110
	If there is an AirCycler™, enter the off / on times.				off on	
	Enter outside air duct pressure.				011	pa
	Type of outside air duct (flex/sheet metal; diameter)					
	Is there an adjustable outside air damper?				Yes No	
	Is there a fireplace or wood stove?				Yes No	
	<u> </u>	Duct location (approximate % in attic, conditioned space, basement, etc.)				
PRESS	SURE TESTING Stack Pressure (baseline with blower door installed; covers on) Dominant Duct Leak Effect (baseline with HVAC system running) Master Bedroom Door Closure Effect (ÄP from main space to outdoors)				pa pa pa	
-	All Doors Closed Effect (ÄP from main space to outdoors)					pa
	Fireplace/Wood Stove Zone HVAC Test					pa
	· ·	Pressure In Each Closed Room (room label and pressure)		pa		pa
				pa		pa
	,					
				pa		pa
				pa		pa
				pa		pa
DI OM	(ED DOOD TESTING (DDT)					
DLOW	/ER DOOR TESTING (BDT) Blower Door Location					
	Total CFM50 (add C & n values if available on multipoint test) CFM50=				C=	n=
	Total Cl W30 (add C & ll V	values II available of	murtipoint test)	CI WISO-	<u> </u>	
DUCT	AIRTIGHTNESS TESTING	(DAT)				
	DAT CFM25 <u>TOTAL</u>	DAT CFM25 <u>TOTAL</u>				
	DAT CFM25 <u>OUTSIDE</u>					
MECH	IANICALS					
MECH	IANI CALS Furnace or air handler	Make:		Model:		

Model:

Domestic hot water

Make:

About this Report This report was produced in cooperation with the US Departments of Energy's Building America Program. Direct all correspondence to: Building Science Corporation, 30 Forest Street, Somerville, MA 02143.

Building Science documents are intended for professionals. The author and the publisher of this article have used their best efforts to provide accurate and authoritative information in regard to the subject matter covered. The author and publisher make no warranty of any kind, expressed or implied, with regard to the information contained in this article.

Limits of Liability and Disclaimer of Warranty:

The information presented in this article must be used with care by professionals who understand the implications of what they are doing. If professional advice or other expert assistance is required, the services of a competent professional shall be sought. The author and publisher shall not be liable in the event of incidental or consequential damages in connection with, or arising from, the use of the information contained within this Building Science document.