#### Joseph Lstiburek, Ph.D., P.Eng, ASHRAE Fellow

# **Building Science**

### Roofs

presented by www.buildingscience.com

### Arrhenius Equation


## For Every 10 Degree K Rise Activation Energy Doubles


 $k = Ae^{-E_a/(RT)}$ 

Damage Functions Water Heat Ultra-violet Radiation


### 2<sup>nd</sup> Law of Thermodynamics


Heat Flow Is From Warm To Cold Moisture Flow Is From Warm To Cold Moisture Flow Is From More To Less Air Flow Is From A Higher Pressure to a Lower Pressure Gravity Acts Down








Water Control Layer Air Control Layer Vapor Control Layer Thermal Control Layer




















































Adapted from Baker, M.; Roofs, 1980; Courtesy National Research Council of Canada
















From Baker, M.; Roofs, 1980
































Adapted from Baker, M.; Roofs, 1980; Courtesy National Research Council of Canada








## Really Heavy Pink Stuff

## Liquid Waterproofing over Concrete Deck


**Building Science Corporation** 


Joseph Lstiburek 47







Joseph Lstiburek 49












Note: Colored shading depicts the building's thermal barrier and pressure boundary. The thermal barrier and pressure boundary enclose the conditioned space.


















































Note: Colored shading depicts the building's thermal barrier and pressure boundary. The thermal barrier and pressure boundary enclose the conditioned space.



Shingles ———

Roofing paper


Minimum R-50 rigid insulation in two or more layers with horizontal and vertical joints staggered


Nail base for shingles (plywood or OSB) screwed through rigid insulation to wood decking or timber rafters


Air barrier membrane -

Wood decking

— Timber rafter or exposed joist












































**Building Science Corporation** 





## Map of DOE's Propused Climate Zones



March 24, 2003

