





High Performance Hybrid Assemblies

Aaron Grin M.A.Sc. P.Eng.
Building Science Corporation
www.buildingscience.com

©2012 Building Science Corporation



Introduction

- 2011 Building America Program
- Evaluation and Testing of Individual Measures for *New Homes*
- Proposed that Hybrid Assemblies would help meet the U.S. Department of Energy home energy use reductions of 30-50%

©2012 Building Science Corporation

2



Building America



The U.S. Department of Energy's Building America Program is reengineering the American home for energy efficiency and affordability. Building America works with the residential building industry to develop and implement innovative building processes and technologies – innovations that save builders and homeowners millions of dollars in construction and energy costs. This industry-led, cost-shared partnership program uses a systems engineering approach to reduce energy use, utility bills, construction time, and construction waste.

For more information, visit our website at:
www.buildingamerica.gov

©2012 Building Science Corporation

3



Why build energy efficient homes?

Consumers:

- Lower energy bills and maintenance costs
- More money for things other than energy
- Healthier, more comfortable, more durable homes

The nation:

- Wise use of resources through energy savings
- Greater energy security through the use of domestic resources
- A healthier environment through reduced emissions
- Increased use of onsite power and renewable energy systems

©2012 Building Science Corporation

4

bsc Overview of the Design approach

Our approach follows three general steps:

-  Step 1: Reduce Enclosure Energy Use
-  Step 2: Reduce Mechanical System Energy Use
-  Step 3: Add Site Generated Energy

©2012 Building Science Corporation 5

bsc Systems Engineered for Zero Cost

Less Cost ← Conventional → More Cost

System	Cost Difference
Advanced Framing	-\$200 SAVINGS
Insulating Sheathing	+\$200 ADDED COST
No Housewrap	-\$200 SAVINGS
High-Performance Solar Control Windows	+\$200 ADDED COST
Compact Duct System	-\$200 SAVINGS
Right Sized Air Conditioner	-\$200 SAVINGS
Air Flow Retarder System	+\$200 ADDED COST
No Poly Vapor Barrier	-\$100 SAVINGS
Controlled Ventilation System	+\$100 ADDED COST
Integrated Heating & Hot Water System	-\$100 SAVINGS
Total Savings	-\$800 SAVINGS

Source: Building America, 1999, Cost Saving System Trade-offs for Mixed Climate, U.S. Department of Energy, Washington, D.C. www.buildingamerica.gov 6

bsc Energy Efficient Construction is Catching on


Total End-Use Residential Energy Consumption in 2001 per Square Foot by Age of Construction

©2012 Building Science Corporation 7

bsc But size matters . . .

- Average House Size in 1940: ~1100 sq ft¹
- Average House Size in 1973: 1660 sq ft²
- Average House Size in 2005: 2434 sq ft

1. Wilson, Alex and Jessica Boehland "Small is Beautiful" *Journal of Industrial Ecology*, Vol 9, No 1-2, 2005
 2. EIA, Annual Energy Review, 2001 data: www.eia.doe.gov/emeu/aer 8



-
- ### Introduction
- Closed Cell Spray Polyurethane Foam is Stiff
 - Some prefabricated builders already use ccSPF for transportation
 - Some builders use ccSPF for condensation control
 - Can ccSPF add structural capacity?
- ©2012 Building Science Corporation 10

-
- ### Introduction
- Research Focus on Hybrid *Wall* Systems
 - Combinations of materials and approaches provide optimum performance
 - No single manufacturer provides all necessary components
 - Integration of materials and manufacturers is key
- ©2012 Building Science Corporation 11

-
- ### Outline
1. Design and Hypothesis
 2. Identification of hybrid wall assemblies
 3. BEopt energy modeling
 4. Thermal analysis
 5. Hygrothermal analysis
 6. Laboratory structural testing
 7. Summary of testing results
 8. Development of Recommendations
- ©2012 Building Science Corporation 12

bsc

Design and Hypothesis

Hybrid walls will utilize a combination of

- 1.5" to 3" exterior board foam insulation
- Diagonal metal strapping
- 2x6 Advanced Framing
- 1.5" closed cell spray polyurethane foam
- Cellulose or fibrous cavity fill insulation
- *No wood based structural sheathing*

©2012 Building Science Corporation 13

bsc

Design and Hypothesis

Hybrid walls can provide effective:

- Thermal control
- Air control
- Moisture control
- Drainage plane
- And Structure!


©2012 Building Science Corporation 14

bsc

Advanced Framing History

The Year – 1854
The Book – The American Cottage Builder

Plate 5.



©2012 Building Science Corporation 15

bsc

Advanced Framing History

1970s

U.S. Department of Housing and Urban Development

NAHB Research Foundation

Operation Break-through delivered “optimum value engineering framing”

Today this is “Advanced Framing”

©2012 Building Science Corporation 16

bsc

Overview

What is Advanced Framing today?

**Framing system on 2' centers
Reduce Framing Material Use
Increases Insulation Volume
Improves Energy Performance
Reduces Labor Costs (eventually)**

©2012 Building Science Corporation

17

bsc

- 24" Centers In-line Framed**
- No Headers in non-load bearing walls**
- Single Studs at Rough Openings**
- No Cripple studs under windows**
- Two Stud Corners**
- Single Insulated Header**
- Header Hangers**
- Single Top Plate**

©2012 Building Science Corporation

18

bsc

Overview

Advanced Framing and The Building Code

Within the IRC the following are permitted:

- 24" On Centre Framing**
- Single Top Plates**
- 24" On Centre Interior Partitions**
- No Headers in Non-Load-Bearing Walls**
- Interior and Exterior Wall Covering on 24" On Centre**
- Drywall Clips**
- Single Headers**

©2012 Building Science Corporation

19

bsc

©2012 Building Science Corporation

20

bsc **Hybrid Wall Assemblies**

		Standard Wall	Exterior Insulated Wall	Hybrid Wall 1	Hybrid Wall 2	Hybrid Wall 3	Hybrid Wall 4	Hybrid Wall 5
Exterior Finish	Any	✓	✓	✓	✓	✓	✓	✓
Drainage	Housewrap Exterior Face of Exterior Insulation, Joints Sealed with Liquid Applied Membrane		✓	✓	✓	✓	✓	✓
Exterior Insulation	1.5" XPS 1.5" FF PIC 8" FF PIC		✓	✓	✓	✓	✓	✓
Structural	7/16" OSB Sheathing Diagonal Metal Strapping + ceSPF	✓	✓	✓	✓	✓	✓	✓
Framing	Advanced Framed	✓	✓	✓	✓	✓	✓	✓
Cavity Insulation 1	1.2" ceSPF			✓	✓	✓	✓	✓
Cavity Insulation 2	Cellulose (damp spray) Spray Fiberglass R21 Fiberglass Batt	✓	✓	✓	✓	✓	✓	✓
Interior Finish	Painted Gypsum	✓	✓	✓	✓	✓	✓	✓

©2012 Building Science Corporation 21


- bsc** **Hybrid Wall 1 and 2**
- Exterior**
- 1.5" XPS Exterior Insulation
 - Diagonal Metal Strapping
 - 2x6 Advanced Framing
 - 1.5" Closed Cell Spray Polyurethane Foam
 - 4" Cellulose (1) or Fiberglass (2)
 - Drywall
- Interior**
- ©2012 Building Science Corporation 22

- bsc** **Hybrid Wall 3 and 4**
- Exterior**
- 1.5" Foil Faced Polyiso Exterior Insulation
 - Diagonal Metal Strapping
 - 2x6 Advanced Framing
 - 1.5" Closed Cell Spray Polyurethane Foam
 - 4" Cellulose (3) or Fiberglass (4)
 - Drywall
- Interior**
- ©2012 Building Science Corporation 23

- bsc** **Hybrid Wall 5**
- Exterior**
- 3" Foil Faced Polyiso Exterior Insulation
 - Diagonal Metal Strapping
 - 2x6 Advanced Framing
 - 1.5" Closed Cell Spray Polyurethane Foam
 - 4" Cellulose
 - Drywall
- Interior**
- ©2012 Building Science Corporation 24

BEopt Analysis

- Average Building America Home
- Modeled in New Orleans and Minneapolis
- Standard Layout and Form
- Average Mechanical Equipment
- Energy Star Appliances
- Average BA Air Tightness
- Only variable changed is the wall R-values



©2012 Building Science Corporation 25

BEopt Specifications


Building Enclosure	
Roof Cladding	Medium colored asphalt shingles
Roof Insulation	R-38 Blown in Fiberglass, vented attic
Walls	Varying
Insulating Sheathing	Varying
Windows	vinyl double glazed with spectrally selective glass (U=0.35, SHGC=0.32)
Infiltration	3.3 ACH 50, 0.23 nACH
Mechanical Systems	
Heat	92.5% AFUE gas furnace, in conditioned space
Cooling	13 SEER air conditioner in conditioned space
DHW	gas tank water heater (EF=0.62)
Ducts	R-6 flex runouts in conditioned space
Ventilation	Central Fan Integrated Supply Ventilation
Appliances, Lighting, MELs	
Lighting	100% Energy Star CFL Package
Appliances	Energy Star Refrigerator, Dishwasher and Clothes Washer

©2012 Building Science Corporation 26

BEopt Analysis - Costs

RSMean CostWorks 2011

- Industry average costs
- Production builders may have better prices







Wall Type	Incremental Construction Cost (\$/ft²)
Standard Wall	\$0.00
Exterior Insulated Wall	\$1.66
Hybrid Wall 1 (1.5\" XPS/Cell)	\$2.30
Hybrid Wall 2 (1.5\" XPS/Fiber)	\$2.39
Hybrid Wall 3 (1.5\" FFRG/Cell)	\$2.20
Hybrid Wall 4 (1.5\" FFRG/Fiber)	\$2.29
Hybrid Wall 5 (3\" FFRG/Cell)	\$5.17

©2012 Building Science Corporation 27

BEopt Analysis - Energy

- Basic House is Building America grade
- Total Package Energy Savings
- Significant portion of savings due to BA Package
- Increments of savings are due to the Hybrid Walls

©2012 Building Science Corporation 28



bsc Thermal Analysis

Therm5 - Clear Wall R-Values Calculated

- **2x6 Advanced Framing**
- **Modeled 16% Framing Factor**

Enclosure Component	Thermal Conductivity k [W/mK]	R-Value Per Inch [hr ² ·F ² /Btu]
Drywall	0.160	0.9
SPF Framing	0.100	1.4
Oriented Strand Board	0.110	1.3
Extruded Polystyrene (XPS)	0.029	5.0
Foil Faced Polyisocyanurate (PIC)	0.022	6.5
2.0 PCF CC Spray Polyurethane Foam	0.024	6.0
Fiberglass - Batt - R21	0.038	3.8
Damp Spray Cellulose	0.037	3.9
Spray Fiberglass	0.034	4.2

©2012 Building Science Corporation 33

bsc Thermal Analysis

Therm5 - Clear Wall R-Values Calculated

©2012 Building Science Corporation 34

bsc Thermal Analysis

Therm5 - Clear Wall R-Values Calculated

Wall Type	Installed R-Value	Clear System Modeled R-Value
Standard Wall	21	18
Exterior Insulated Wall	26	25
Hybrid Wall 1	30	28
Hybrid Wall 2	31	28
Hybrid Wall 3	34	30
Hybrid Wall 4	35	31
Hybrid Wall 5	43	40

©2012 Building Science Corporation 35

bsc Thermal Analysis

Therm5 - Clear Wall R-Values Calculated

- **Hybrid Walls improve R-Value**
- **Hybrid Wall 5 improves the most**
- **Hybrid Wall 4 improves second most**
- **More Analysis Required**

©2012 Building Science Corporation 36

bsc **Hygrothermal Analysis**

WUFI

Most advanced commercially available hygrothermal moisture modeling program

Modeling

- Two Base Walls
- Five Hybrid Walls
- Two Exterior Climates
- Two Interior Humidity Cases
- One Interior Temperature Profile

Looking to compare Temperature and Dew Point profiles

©2012 Building Science Corporation 37

bsc **Hygrothermal Analysis**

Two Exterior Climates

- **New Orleans**
 - Temp - Mean 67° F, Max 95° F, Min 21° F
 - RH - Mean 72%
 - Rainfall - 57.5 inches
- **Minneapolis**
 - Temp - Mean 43° F, Max 95° F, Min -26° F
 - RH - Mean 72%
 - Rainfall - 40 inches

©2012 Building Science Corporation 38

bsc **Hygrothermal Analysis**

Two Humidity Cases

- Low - 30% Winter, 60% Summer - Sinusoidal
- High - 40% Winter, 70% Summer - Sinusoidal

Relative Humidity

Adjustments	
Mean Value [%]	45
Amplitude [%]	15
Day of Maximum	16,08/2012

Constant

©2012 Building Science Corporation 39

bsc **Hygrothermal Analysis**

Criteria Monitored

- Condensation Plane Temperature
- Interior Temperature and Relative Humidity

Calculations

- Interior Air Dew point

Comparisons and Risk

- Air leakage condensation risk
- Air leakage must be present
- Duration, repetition, alternating drying




©2012 Building Science Corporation 40





bsc **Hygrothermal Analysis**




Air leakage condensation - air leakage must be present



©2012 Building Science Corporation 41







Hygrothermal Analysis

Summary

- Hybrid Walls significantly reduced risk
- Hybrid Wall 5 reduced risk the most
- Hybrid Wall 3 reduced risk the second most
- New Orleans showed no condensation risks
- Only a little more analysis!

©2012 Building Science Corporation 52

bsc

Structural Analysis

ASTM E72 Testing

Standard Test Methods of Conducting Strength Tests of Panels for Building Construction

aka – Racking Tests

 - Midland, Michigan

Build and Test

- Base Case Code Accepted Wall
- Base Case Strapping Only Wall
- Hybrid Walls

©2012 Building Science Corporation

53

bsc

Structural Analysis

Comparison and Analysis

- Base Case Test 0 – 3 Walls
- Base Case Test 1 Strapping Only – 3 Walls
- Hybrid Test 2 with XPS Exterior Insulation – 3 Walls
- Hybrid Test 3 with ffPIC Exterior Insulation – 3 Walls

No Cellulose or Fiberglass

No Drywall

No Exterior Finish

©2012 Building Science Corporation

54

bsc

Structural Analysis

Comparison and Analysis

All Walls Tested are 8' High and 8' Wide

Base Case – 3 Walls

- 2x6 Advanced Framing
- 7/16" OSB Sheathing

Base Case Strapping Only – 3 Walls

- 2x6 Advanced Framing
- Diagonal 16 Gauge Metal Strapping
- 1.5" XPS Insulating Sheathing

©2012 Building Science Corporation

55

bsc

Structural Analysis

Comparison and Analysis

All Walls Tested are 8' High and 8' Wide

Hybrid Wall Structural Test 2 – 3 Walls




- 2x6 Advanced Framing
- Diagonal 16 Gauge Metal Strapping
- 1.5" XPS Insulating Sheathing
- 1.5" ccSPF Insulation

Hybrid Wall Structural Test 3 – 3 Walls





- 1.5" ffPIC Insulating Sheathing

©2012 Building Science Corporation

56



-
- bsc** **Structural Analysis**
- ASTM E72 Racking Testing**
 Deflection as a result of loadings
- Ram locates wall and zeros its displacement measurement
 - Loadings applied 395 lbs/minute
 - Loading to 790lbs
 - Release loading
 - Loading to 1570 lbs
 - Release loading
 - Loading to 2360 lbs
 - Release loading
 - Load to failure (4" deflection or 30,000 lbs)
- ©2012 Building Science Corporation 60



bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation




©2012 Building Science Corporation

65

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation



©2012 Building Science Corporation

66

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation



©2012 Building Science Corporation

67

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation




©2012 Building Science Corporation

68

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation



©2012 Building Science Corporation 69

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation




©2012 Building Science Corporation 70

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation



©2012 Building Science Corporation 71

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation



©2012 Building Science Corporation 72

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation



©2012 Building Science Corporation

73

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation



©2012 Building Science Corporation

74

bsc

Structural Analysis

Base Case 1 – XPS Exterior Insulation



©2012 Building Science Corporation

75

bsc





Structural Analysis

Base Case 1 – XPS Exterior Insulation



©2012 Building Science Corporation

76



bsc

Structural Analysis

Hybrid Test 2 – XPS Exterior Insulation



©2012 Building Science Corporation

81

bsc

Structural Analysis

Hybrid Test 2 – XPS Exterior Insulation



©2012 Building Science Corporation

82

bsc

Structural Analysis

Hybrid Test 2 – XPS Exterior Insulation



©2012 Building Science Corporation

83

bsc





Structural Analysis





Hybrid Test 2 – XPS Exterior Insulation



©2012 Building Science Corporation

84





bsc

Structural Analysis

Hybrid Test 3 – ffPIC Exterior Insulation



©2012 Building Science Corporation

93

bsc

Structural Analysis

Hybrid Test 3 – ffPIC Exterior Insulation



©2012 Building Science Corporation

94

bsc

Structural Analysis

Hybrid Test 3 – ffPIC Exterior Insulation



©2012 Building Science Corporation

95

bsc





Structural Analysis

Hybrid Test 3 – ffPIC Exterior Insulation



©2012 Building Science Corporation

96





Analysis Summary

BEopt Hybrid Walls

- \$2.20/ft² to \$5.17/ft²
- Wall 5 – 3” ffPIC highest cost
- \$2.20/ft² to \$2.30/ft² (w/o Wall 5)
- 3% to 5% Annual Energy Savings
- Tight group of Annualized Energy Costs
- Wall 5 Ruled Out
- No Clear Wining Wall

©2012 Building Science Corporation

101



Analysis Summary

Thermal

- All Hybrid walls outperform Base Cases
- Hybrid Wall 5 highest R-Value
- Hybrid Wall 3 and 4 Second Highest R-Value

Hygrothermal

- All Hybrid walls outperform Base Cases
- Hybrid Wall 5 Lowest Condensation Risk
- Hybrid Wall 3 and 4 Second Lowest
- Hybrid Wall 3 – 98% Reduction in Risk

©2012 Building Science Corporation

102



Analysis Summary

Structural

- XPS and Strapping Capacity ~ 2000lbs @ 3.5”
- 7/16” OSB Capacity ~ 4000 lbs @ 2.5”
- XPS and ccPSF Capacity ~ 6000 lbs @ 2”
- ffPIC and ccSPF Capacity ~ 6000 lbs @ 1.5”
- Hybrid Walls 3 and 4 use ffPIC

©2012 Building Science Corporation

103



Analysis Summary

Hybrid Wall 3 – Best Performer

- 1.5” ffPIC Exterior Insulation
- 26 Gauge Diagonal Metal Strapping
- 2x6 Advanced Framing
- 1.5” ccSPF Insulation
- 4” Cellulose Cavity Fill Insulation
- Drywall

©2012 Building Science Corporation

104



Further Research

- Structural capacity of hybrid walls without diagonal strapping
- Structural capacity of hybrid walls with full cavity closed cell spray foam
- Structural capacity of hybrid walls with various stud fasteners
- Cyclic seismic structural capacities of hybrid assemblies
- Flood repair options for hybrid assemblies
- Full scale wind testing of homes with hybrid walls

©2012 Building Science Corporation 105



Thank You

Questions?

For more information and the full report visit

buildingscience.com

<p>information</p> <p style="font-size: x-small;">provides objective, high-quality information to promote the design and construction of durable, healthy, energy-efficient and economical buildings</p>	<p>consulting</p> <p style="font-size: x-small;">provides consulting services in the areas of architecture, building diagnostics, investigations, education and training, and material science analysis</p>
<p>bookstore</p> <p style="font-size: x-small;">offers publications related to building science including moisture management, building envelopes, ergonomics, water management and ventilation</p>	<p>seminars</p> <p style="font-size: x-small;">offers one- to two-day seminars that focus on either introductory building science topics or advanced building science progress and practices</p>

©2012 Building Science Corporation 106